



Date of Issue: 3/9/2023 Report Number: 23-000734

Revision Number:1

Date Order Received: 03/06/2023

Sponsor: Westbury Textiles USA Inc

c/o Sobel & Co 50 Tice Blvd STE 175

Woodcliff Lake, NJ 07677-7681

Sponsor's Identification:

Villandry FR

CERTIFICATE OF TESTING

TEST PERFORMED: IMO 2010 FTP Code, Part 8 - Test for upholstered furniture

TEST RESULTS

	Progressive	Flaming (Y/N)	Char Length (mm	
Specimen	Smoldering (Y/N))	
1	No	No	13	
2	No	No	12	

	Flaming* (s)	Glowing* (s)	Smoking* (s)	Smoldering*	Char Length
Specimen				(s)	(mm)
1	0	0	2	0	38
2	0	0	3	0	34

NOTES

Test Conditions: 70 ±4°F, 65 ±5% Relative Humidity

Sampling Method: As Received Deviations: None

Test Item Composite Filling Material -

☐ Non flame retardant flexible polyether foam, 22 kg/m3 (1.4 lb/ft3)

☑ Flame retardant polyurethane foam, CMHR, 35 kg/m3 (2.2 lb/ft3)

☐ Client's filling material

ACCEPTANCE CRITERIA

Smoldering Ignition Source

1. Progressive smoldering or flaming must cease within one hour after start of test

Flaming Ignition Source

1. Flaming, glowing, smoking or smoldering may not exceed 120 seconds

CONCLUSION Based on the above results and failure criteria, the item tested:

☑ Meets the requirements - May be labeled IMO FTPC Part 8

☐ Does not meet the requirement

CERTIFICATION I certify that the above results were obtained after testing specimen in accordance with the procedures and equipment specified by the standard stated above. The test results relate to the behavior of the test specimens of a product under the particular conditions of the test; they are not intended to be the sole criterion for assessing the potential fire hazard of the product in use.

Jorda Stiven
Authorized Signature

553 76th Street, Byron Center, MI 49315

P: 616-559-6123 E: testlab@applied-lab.com

Page 1 of 2

Date Order Completed: 03/08/2023

APPENDIX

Company Submitting Testing

Westbury Textiles USA Inc C/o Sobel & Co 50 Tice Blvd STE 175 Woodcliff Lake NJ 07677-

7681 USA

End Use

Manufacturer of MaterialUnknownProduct IdentificationVillandry FRColor SubmittedLight Sable

Color Submitted Light Sable
Weight of Fabric 600 Grams per sq meter

Material Thickness

Coating Type + Weight

None

Upholstery (Not Specified)

Method + Qty of Fire

Retardant Treatment
Content
No FR Treatment
100% Polyester FR
Weave Type
Twill Weave

Pick + End Count

Yarn Type / Count
The Appendix information above is provided by the Sponsor and is not determined by Applied Lab.

Date Sample Arrived 3/6/23

Cleaning / Weathering Procedure

Date of Test 3/8/23

Cigarette Used NIST SRM 1196

Length: 70 ±4mm, Diameter: 8 ± 0.5mm, Mass: 0.95 ± 0.15g,

Smoldering rate: 11 ± 4.0 min / 50mm