



Date of Issue: 3/25/2024 Report Number: 24-000658

Revision Number:1

Date Order Received: 03/19/2024

For the Account of: Westbury Textiles USA Inc

c/o Sobel & Co

50 Tice Blvd STE 175

Woodcliff Lake, NJ 07677-7681

Client's Identification: Vi
-----------------------------

## **CERTIFICATE OF TESTING**

TEST PERFORMED: NFPA 701 Standard Methods of Fire Test for Flame Propagation of Textiles and Films 2019 – Test #1

## **TEST RESULTS**

Specimen	Mass Initial (g)	Mass Final (g)	Mass Loss (%)	Drip Burn (s)	Afterflame (s)
1	39.2	33.3	15	0.0	0.0
2	40.0	36.7	8	0.0	0.0
3	38.9	35.3	9	0.0	0.0
4	38.7	34.5	11	0.0	0.0
5	39.1	36.5	7	0.0	0.0
6	39.1	35.5	9	0.0	0.0
7	38.5	34.0	12	0.0	0.0
8	38.8	36.4	6	0.0	0.0
9	38.5	31.1	19	0.0	0.0
10	38.7	33.7	13	0.0	0.0
Average	39.0	34.7	11	0.0	0.0

Approximate weight (oz./so	<b>q. yd):</b> 19.2	Standard Deviation: 4.0	Average + 3 SD: 23.0
Product Configuration: Conditioning: ntended End-use (if know	⊠ Single Layer ⊠ Oven at 220°F fo n & other than drapery): Dra	☐ Multi Layer r minimum 30 minutes apery	☐ 70 ±2°F & 65 ±2%RH for minimum 24 hours
<ol> <li>Where fragments seconds per spectors.</li> <li>Where the averages.</li> <li>Individual speciments.</li> <li>Where the speciments be recorded as particular to the second second.</li> </ol>	or residues of specimens the simen for the sample of 10 species weight loss of the 10 species will be listed as a failure nens do not demonstrate per assing this test and shall be con the above Results and Action	pecimens, the material shall be rec simens in a sample is greater than if it exceeds mean + 3 SD	per continue to burn for more than an average of 2 orded as failing. (Flaming Drip) 40 percent, the material shall be recorded as failing.  er of the conditions indicated above, the material shall
Specified by the standard st		tained after testing specimen in ac	cordance with the procedures and equipment
Authorized Signature			Date Order Completed: 03/21/2024